



Features

- Wide temperature range -55°C to 125°C^*
- Thermoset Insulation
- Superior mechanical properties
- Flexible construction
- Flame retardant
- Excellent fluid/oil resistance
- Moisture and sunlight resistant

Performance Standards

- AAR S-501
- AAR RP-585
- ICEA S-66-524 (5-95-658)
- Passes UL VW-1 flame test
- Passes IEEE-383 1974 vertical tray flame test
- Meets requirements of 49 CFR Part 238 for flame and smoke requirements
- Meets transit toxicity requirements when tested in accordance with BSS 7239

Construction

Conductor: Annealed, Tinned copper per ASTM B33, B172, AAR S-501, and AAR RP-585

Insulation: Crosslinked polyolefin, Exane® (colors — as required)

Rated 125°C , maximum 130°C overload, 250°C short circuit

Scope

Exane®-1069A Diesel Cable is a tough, flame retardant construction ideally suited for rugged, railroad diesel electric locomotive applications. It has a high temperature rating yet will not crack at temperatures down to -55°C . Exane® Diesel Locomotive Cable has much better resistance to cut-through, crush, and scrape abrasion than rubber, EPR, Neoprene and Hypalon. It is also more flexible and has better overload characteristics than fluoropolymers. Exane® has good moisture and oil resistance, excellent fire resistance, low smoke and acid gas generation characteristics, and resists stress cracking and conduits. RHW-2 walls meet UL requirements and provide enhanced mechanical toughness.



CHICAGO

933 E. Remington Rd
Schaumburg, IL 60173
847.944.1500

BOSTON

100 Jytek Drive
Leominster, MA 01453
978.534.5300

ATLANTA

5940 Cabot Parkway
Alpharetta, GA 30005
678.297.1080

PHOENIX

1524 W 14th St
Tempe, AZ 85281
623.478.8700

Exane[®]-1069A

125°C* Locomotive Wire



600 Volt and 2000 Volt
AAR S-501/RP-585
(XLPO)
Spec. DAA1069A

600 Volt Class

Product Number	Conductor Size (AWG)	Stranding	(mm ²)	Insulation Wall (Inch)	(mm)	Nom. Diameter (Inch)	(mm)	Aprox. Weight (#/m')	(kg/km)
LXE-18-600V	18	19/30	.96	.030	.76	0.109	2.76	11	16.4
LXE-16-600V	16	19/29	1.22	.030	.76	0.116	2.94	13	19.3
LXE-14-600V	14	37/29	2.40	.030	.76	0.137	3.47	21	31.3
LXE-12-600V	12	37/27	3.77	.030	.76	0.157	3.98	29	43.2
LXE-10-600V	10	27/24	5.53	.030	.76	0.178	4.52	44	65.5

2000 Volt Class

Product Number	Conductor Size (AWG)	Stranding	(mm ²)	Insulation Wall (Inch)	(mm)	Nom. Diameter (Inch)	(mm)	Aprox. Weight (#/m')	(kg/km)
LXE-18-2KV	18	19/30	.96	.045	1.14	0.139	3.53	15	22.3
LXE-16-2KV	16	19/29	1.22	.045	1.14	0.144	3.65	17	25.3
LXE-14-2KV	14	37/29	2.40	.045	1.14	0.164	4.16	25	37.2
LXE-12-2KV	12	37/27	3.77	.045	1.14	0.187	4.75	34	50.6
LXE-10-2KV	10	27/24	5.53	.045	1.14	0.208	5.28	51	75.9
LXE-8-2KV	8	37/24	7.57	.055	1.40	0.252	6.40	71	105.7
LXE-5-2KV	5	91/24	19	.055	1.40	0.354	8.99	149	221.7
LXE-3-2KV	3	125/24	26	.055	1.40	0.401	10.18	204	303.6
LXE-1-2KV	1	225/24	46	.065	1.65	0.522	13.25	354	526.8
LXE-2/0-2KV	2/0	325/24	66	.065	1.65	0.578	14.68	494	735.1
LXE-4/0-2KV	4/0	550/24	112	.105	2.67	0.792	20.11	851	1266.4
LXE-313-2KV	313MCM	775/24	159	.105	2.67	0.917	23.29	1131	1683.0
LXE-444-2KV	444MCM	1100/24	225	.105	2.67	1.042	26.46	1607	2391.4
LXE-535-2KV	535MCM	1325/24	271	.120	3.18	1.149	29.18	2000	2976.2
LXE-592-2KV	597MCM	1480/24	303	.125	3.18	1.234	31.34	2200	3273.8

1. The Exane[®] insulation family has outstanding mechanical and electrical, long-term moisture, and heat aging characteristics. See the above specification for details.



CHICAGO

933 E. Remington Rd
Schaumburg, IL 60173
847.944.1500

BOSTON

100 Jytek Drive
Leominster, MA 01453
978.534.5300

ATLANTA

5940 Cabot Parkway
Alpharetta, GA 30005
678.297.1080

PHOENIX

1524 W 14th St
Tempe, AZ 85281
623.478.8700

For sales inquiries: sales@electrowire.com